PATENT COOPERATION TREATY,

PCT

REC'D 17 MAR 2005

PCT

INTERNATIONAL PRELIMINARY EXAMINATION PEPORT

(PCT Article 36 and Rule 70)

Applic	Applicant's or agent's file reference EOP FUDTHER ACTION See Notification of Transmittal of International							
P 02 119 WO				FOR FURTHER A	CTION		amination Report (Form PCT/IPE/	A/416)
International application No. PCT/DK 02/00831				International filing date 09.12.2002	(day/monti	h/year)	Priority date (day/month/year) 09.12.2002	
International Patent Classification (IPC) or both national classification and IPC H03G5/00								
Applicant								
TC ELECTRONIC A/S et al.								
1.	. This international preliminary examination report has been prepared by this International Preliminary Examining							
	Authority and is transmitted to the applicant according to Article 36.							'9
2.	This	REPO	DRT consists of a total o	of 5 sheets including t	nis cover	sheet		
	This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).							
	These annexes consist of a total of 4 sheets.							
3.	This	repor	t contains indications rel	ating to the following it	ems:			
	1	I ☒ Basis of the opinion						
	11		Priority					
	Ш		Non-establishment of o	pinion with regard to n	ovelty, in	ventive step a	nd industrial applicability	
	IV		Lack of unity of invention	on				
	V 🖾 Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement						cability;	
	VI		Certain documents cite	ed				
	VII		Certain defects in the in	nternational application	1			
	VIII Certain observations on the international application							
Date of submission of the demand					Date of o	completion of this	s report	
17.06.2004					16.03.2005			
Name and mailing address of the international preliminary examining authority:					Authorize	ed Officer		chas Petenton
European Patent Office							11 1	
D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d					Hartbe	rger, J	e,mana ¹	
Fax: +49 89 2399 - 4465					Telephoi	ne No. +49 89 2	399-2193	Mann a MID . offi

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/DK 02/00831

I.	Basis	of the	report
----	--------------	--------	--------

1. With regard to the **elements** of the international application (Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17)):

	Des	Description, Pages								
	1-28		as origi	as originally filed						
	Clo	ims, Numbers								
		·								
	1-23	3	receive	d on 17.12.2004 with letter of 15.12.2004						
	Dra	Orawings, Sheets								
	1/6-	6/6	as origi	nally filed						
2.	With lang	n regard to the langu juage in which the int	the language , all the elements marked above were available or furnished to this Authority in the international application was filed, unless otherwise indicated under this item.							
	The	se elements were av	elements were available or furnished to this Authority in the following langu							
		the language of a tra	anslation furnish	ed for the purposes of the international search (ur	der Rule 23.1(b)).					
		the language of publ	ication of the int	ternational application (under Rule 48.3(b)).						
		the language of a tra Rule 55.2 and/or 55.		ed for the purposes of international preliminary ex	amination (under					
3.	With inte	regard to any nucleotide and/or amino acid sequence disclosed in the international application, the national preliminary examination was carried out on the basis of the sequence listing:								
		\square contained in the international application in written form.								
	\Box filed together with the international application in computer readable form.									
	☐ furnished subsequently to this Authority in written form.									
	furnished subsequently to this Authority in computer readable form.									
		The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.								
	☐ The statement that the information recorded in computer readable form is identical to the written listing has been furnished.				the written sequence					
4.	The	he amendments have resulted in the cancellation of:								
		the description,	pages:	-						
	\boxtimes	the claims,	Nos.:	24-26						
		the drawings,	sheets:							

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/DK 02/00831

5. This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)).

(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)

6. Additional observations, if necessary:

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N) Yes: Claims 1-23

No: Claims

Inventive step (IS) Yes: Claims 1-23

No: Claims

Industrial applicability (IA) Yes: Claims 1-23

No: Claims

2. Citations and explanations

see separate sheet

Re Item V

1

Reasoned statement with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

Reference is made to the following documents: 1.

D1: US-A-6 163 789 D2: US-A-4 891 841

Document D1, which is considered to represent the most relevant state of the art, 2. discloses (cf. Figs. 3, 5, and 6, and the description column 1, lines 16-49, column 2, lines 18-48 and column 3, lines 10, to column 4, line 48) an parametric equalizer from which the subject-matter of Claim 1 differs in that said parametric equalizer comprising further means for adjusting a symmetry parameter independent to the other user parameter, which may be continuously varied in order to provide a smooth transition between "low-shelf", "bell-shaped" and "high-shelf" filter characteristic of said at least one filter block (FIB).

The subject-matter of Claim 1 is therefore new (Article 33(2) PCT).

The problem to be solved by the present invention may be regarded as to obtain a 3. user friendly way of adjusting a parametric equalizer, in particular by adjusting a further parameter which may be continuously varied independent from the other three parameters to provide a smooth transition between different filter characteristics of the at least one filter block.

The solution to this problem proposed in Claim 1 of the present application is not rendered obvious from the available prior art, in particular from D1 or D2 alone, or in combination of this two documents.

The subject-matter of Claim 1 is thus considered as involving an inventive step (Article 33(3) PCT).

- Claims 2 to 23 are dependent on Claim 1 and as such also meet the requirements 4. of the PCT with respect to novelty and inventive step.
- The industrial applicability of the subject-matter as claimed is not doubted. 5.

INTERNATIONAL PRELIMINARY International application No. PCT/DK 02/00831 EXAMINATION REPORT - SEPARATE SHEET

6. For the sake of completeness the following is noted:

1

- The description is not in conformity with the claims as required by Rule 5.1(a)(iii) PCT;
- Contrary to the requirements of Rule 5.1(a)(ii) PCT, the relevant background art disclosed in the documents D1 and D2 is not mentioned in the description, nor are these documents identified therein.
- Furthermore, taking into account the bell shaped filter responses in Figures 2d-3b it appears that f_c in these cases should be understood to mean the center frequency rather than the corner frequency, which is presently not defined in the claims (Art. 6 PCT)

5

15

30

Amended Claims (15 December 2004)

1. Parametric equalizer comprising

filtering means (FM), user interface means (UIM), audio signal input means and audio signal output means,

said filtering means comprising at least one filter block (FIB)

said user interface means (UIM) comprising means for adjustment of first, second and third independent user parameters: corner frequency (fc), shape (Q) and gain (G),

said parametric equalizer comprising further means for adjusting a symmetry parameter independent to the other user parameters, which may be continuously varied in order to provide a smooth transition between low-shelf, bell-shaped and high-shelf filter characteristic of said at least one filter block (FIB).

- 2. Parametric equalizer according to claim 1, wherein
- said user interface means (UIM) comprises a further symmetry adjustment parameter (SYM) for establishing a variable symmetry of the magnitude response of said at least one filter block (FIB),
- said user interface means is mapped by means of coefficient adjustment algorithms into filter coefficient settings (FCS) of the at least one filter block (FIB), which when established reflects the adjustment of the user interface means (UIM)
 - said further adjustment parameter (SYM) provides a filter coefficient setting (FCS) comprising a combined adjustment of at least one zero frequency, pole frequency, zero Q and pole Q of the magnitude response of said at least one filter block.

- 3. Parametric equalizer according to claim 1 or 2, wherein
- said user control means facilitates adjustment of corner frequency (fc), Shape (Q), gain and symmetry.
 - 4. Parametric equalizer according to any of claims 1-3, wherein said filter coefficient settings (FCS) comprise digital coefficients.
- 5. Parametric equalizer according to any of the claims 1-4, wherein said filter coefficient settings (FCS) comprise analogue values established by means of adjustable or selectable filter components of said at least one filtering means.
- 6. Parametric equalizer according to any of the claims 1-5, wherein
 said filtering means comprises less than twenty individually adjustable filter blocks
 (FIB), preferably less that ten and most preferably less than six.
 - 7. Parametric equalizer according to any of the claims 1-6, wherein at least one of said filtering blocks comprise a biquatic filter.
 - 8. Parametric equalizer according to any of the claims 1-7, wherein said parametric equalizer comprises at least one, preferably at least three cascaded biquadratic filters blocks (FIB).
- 9. Parametric equalizer according to any of the claims 1-8, wherein said filtering means is analogously implemented.
 - 10. Parametric equalizer according to any of the claims 1-9, wherein said filtering means is digitally implemented.

20

11. Parametric equalizer according to any of the claims 1-10, wherein said filtering means comprises gain compensation means adapted for compensation of alteration of the filtering block gain invoked by a changed setting of the further adjustment parameter.

5

12. Parametric equalizer according to any of the claims 1-11, wherein said filtering means comprises comer frequency compensation means adapted for compensation of alteration of the corner frequency of the filtering block invoked by a changed setting of the further adjustment parameter.

10

- 13. Parametric equalizer according to any of the claims 1-12, wherein said user interface provides at least four different asymmetries of filter setting at least in part of the frequency range.
- 14. Parametric equalizer according to any of the claims 1-13, wherein said further adjustment parameter (SYM) enables the user to gradually transform the filter block (FIB) between a low-shelf and a high-shelf filter characteristic.
- 15. Parametric equalizer according to any of the claims 1-13, wherein
 20 said further adjustment parameter (SYM) enables the user to gradually transform the
 filter block (FIB) from a low-shelf into a bell-shape and further into a high-shelf,
 thus defining at least one more than said three standard filter types.
- 16. Parametric equalizer according to any of the claims 1-15, wherein the number of said adjustment parameters corresponds the number of non-trivial degrees of freedom of the at least one filter block (FIB).
 - 17. Parametric equalizer according to any of the claims 1-16, wherein the number of said adjustment parameters is at least the number of non-trivial degrees of freedom of

10

15

the at least biquad filter block (FIB) times the number of filter blocks (FIB) of said filtering means.

- 18. Parametric equalizer according to any of the claims 1-17, wherein the number of
 non-trivial degrees of freedom of each of a number of cascaded filter block is at least four.
 - 19. Parametric equalizer according to any of the claims 1-18, wherein the symmetry parameter may be set by means of the user interface to at least four different values, preferably a continuos interval of values in the digital or analog embodiment.
 - 20. Parametric equalizer according to any of the claims 1-19, wherein the adjustment parameters are converted into filter coefficient settings (FCS) triggered by the setting of the adjustment parameters by the user.
 - 21. Parametric equalizer according to any of the claims 1-20, wherein the conversion of adjustment parameters into filter coefficient settings is invertible.
- 22. Parametric equalizer according to any of the claims 1-21, wherein
 NDOFpar ≥ NDOFcoef,
 - where NDOFpar is the number of adjustable equalizer parameters and NDOFcoef is the number of non-trivial degrees of freedom (fc, G, Q, Sym).
- 23. Parametric equalizer according to any of the claims 1-22, wherein given filter coefficient settings may be converted into corresponding adjustment parameters.